

Wind Mitigation Inspection Certificate

01/26/2023 Inspection Date

Golfvista Condominium Association
Homeowner



934 Capri Isles Blvd Street Address

Venice

City

Sarasota

Zip Code

www.windmitigation.network 239 351 5513

Anyone utilizing this certificate, you understand and agree: Inspections we perform are visual documenting the information requested on the OIR-B1-1802 form. Wind Mitigation Network, Llc and our network of inspection companies make no warranty, expressed or implied, that new insurance premiums will be higher or lower. Any liability of our and our network of inspection company's performance is expressly limited to the inspection fee paid. If you have any questions please email: info@windmitigations.com.

Uniform Mitigation Verification Inspection Form

Maintain a copy of this form and any documentation provided with the insurance policy

Inspection Date: 01/26/2023									
Owner Information MASTER CERTIFICATE									
Owner Name: Golfvista Condominium Association Contact Person:									
Address: 934 Capri Isles Blvd	Home Phone:								
City: Venice	Zip: Sarasota		Work Phone:						
County: Sarasota			Cell Phone: 941-221-	-1599					
Insurance Company:			Policy #:						
Year of Home: 1990	# of Stories: 2		Email: Ronald@argu	isvenice.com					
accompany this form. At least one photog though 7. The insurer may ask additional	NOTE: Any documentation used in validating the compliance or existence of each construction or mitigation attribute must accompany this form. At least one photograph must accompany this form to validate each attribute marked in questions 3 though 7. The insurer may ask additional questions regarding the mitigated feature(s) verified on this form.								
1. <u>Building Code</u> : Was the structure built the HVHZ (Miami-Dade or Broward cou ☐ A. Built in compliance with the FBC	inties), South Florida E C: Year Built	Building Code (SFB For homes built	C-94)? t in 2002/2003 provide a per						
a date after 3/1/2002: Building Perm ☐ B. For the HVHZ Only: Built in comprovide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application with a discontinuous content of the second provide a permit application and the second provide a p	appliance with the SFBO late after 9/1/1994: Bu	C-94: Year Builtilding Permit Applic	For homes built in 19	994, 1995, and 1996					
C. Unknown or does not meet the red	quirements of Answer	"A" or "B"							
2. Roof Covering: Select all roof covering OR Year of Original Installation/Replace covering identified.		no information was	s available to verify complia						
	Application Date	FBC or MDC Product Approval #	Year of Original Installation or Replacement	No Information Provided for Compliance					
1. Asphalt/Fiberglass Shingle									
	07/2022		2022						
П									
A. All roof coverings listed above m installation OR have a roofing permi	eet the FBC with a FB it application date on o	r after 3/1/02 OR th	e roof is original and built in	rent at time of 1 2004 or later.					
☐ B. All roof coverings have a Miamiroofing permit application after 9/1/1	Dade Product Approva 1994 and before 3/1/20	al listing current at t 002 OR the roof is or	ime of installation OR (for t riginal and built in 1997 or l	he HVHZ only) a ater.					
\Box C. One or more roof coverings do no	ot meet the requiremen	ts of Answer "A" or	r "B".						
☐ D. No roof coverings meet the require	rements of Answer "A	" or "B".							
3. Roof Deck Attachment : What is the we	akest form of roof dec	k attachment?							
A. Plywood/Oriented strand board (OSB) roof sheathing attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by staples or 6d nails spaced at 6" along the edge and 12" in the fieldOR- Batten decking supporting wood shakes or wood shinglesOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that has an equivalent mean uplift less than that required for Options B or C below.									
B. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 12" inches in the fieldOR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent or greater resistance than 8d nails spaced a maximum of 12 inches in the field or has a mean uplift resistance of at least 103 psf.									
C. Plywood/OSB roof sheathing with a minimum thickness of 7/16" inch attached to the roof truss/rafter (spaced a maximum of 24" inches o.c.) by 8d common nails spaced a maximum of 6" inches in the fieldOR- Dimensional lumber/Tongue & Groove decking with a minimum of 2 nails per board (or 1 nail per board if each board is equal to or less than 6 inches in width)OR- Any system of screws, nails, adhesives, other deck fastening system or truss/rafter spacing that is shown to have an equivalent									
Inspectors Initials AHP Property Address 934 Capri Isles Blvd Venice Sarasota									

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure. OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155 Page 1 of 4

		or greater resistance than 8d common nails spaced a maximum of 6 inches in the field or has a mean uplift resistance of at least 182 psf.
		D. Reinforced Concrete Roof Deck.
		E. Other:
		F. Unknown or unidentified.
		G. No attic access.
4.		of to Wall Attachment: What is the <u>WEAKEST</u> roof to wall connection? (Do not include attachment of hip/valley jacks within the of the inside or outside corner of the roof in determination of WEAKEST type)
		A. Toe Nails
		☐ Truss/rafter anchored to top plate of wall using nails driven at an angle through the truss/rafter and attached to the top plate of the wall, or
		☐ Metal connectors that do not meet the minimal conditions or requirements of B, C, or D
	Mi	nimal conditions to qualify for categories B, C, or D. All visible metal connectors are:
		Secured to truss/rafter with a minimum of three (3) nails, and
		Attached to the wall top plate of the wall framing, or embedded in the bond beam, with less than a ½" gap from the blocking or truss/rafter and blocked no more than 1.5" of the truss/rafter, and free of visible severe corrosion.
	X	B. Clips
		Metal connectors that do not wrap over the top of the truss/rafter, or
		☐ Metal connectors with a minimum of 1 strap that wraps over the top of the truss/rafter and does not meet the nail position requirements of C or D, but is secured with a minimum of 3 nails.
		C. Single Wraps Metal connectors consisting of a single strap that wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side and a minimum of 1 nail on the opposing side.
	П	D. Double Wraps
		Metal Connectors consisting of 2 separate straps that are attached to the wall frame, or embedded in the bond beam, on either side of the truss/rafter where each strap wraps over the top of the truss/rafter and is secured with a minimum of 2 nails on the front side, and a minimum of 1 nail on the opposing side, or
		☐ Metal connectors consisting of a single strap that wraps over the top of the truss/rafter, is secured to the wall on both sides, and is secured to the top plate with a minimum of three nails on each side.
		E. Structural Anchor bolts structurally connected or reinforced concrete roof.F. Other:
		G. Unknown or unidentified
		H. No attic access
5.		of Geometry: What is the roof shape? (Do not consider roofs of porches or carports that are attached only to the fascia or wall of host structure over unenclosed space in the determination of roof perimeter or roof area for roof geometry classification).
	X	A. Hip Roof Hip roof with no other roof shapes greater than 10% of the total roof system perimeter.
		Total length of non-hip features: feet; Total roof system perimeter: feet B. Flat Roof Roof on a building with 5 or more units where at least 90% of the main roof area has a roof slope of
		less than 2:12. Roof area with slope less than 2:12 sq ft; Total roof area sq ft C. Other Roof Any roof that does not qualify as either (A) or (B) above.
6.		 ondary Water Resistance (SWR): (standard underlayments or hot-mopped felts do not qualify as an SWR) A. SWR (also called Sealed Roof Deck) Self-adhering polymer modified-bitumen roofing underlayment applied directly to the sheathing or foam adhesive SWR barrier (not foamed-on insulation) applied as a supplemental means to protect the dwelling from water intrusion in the event of roof covering loss. B. No SWR. C. Unknown or undetermined.
		A TANK AND BOOK AND 034 Caprillates Plyd Vanice Serecto
ĺn	spec	tors Initials AHP Property Address 934 Capri Isles Blvd Venice Sarasota
* Т	This	verification form is valid for up to five (5) years provided no material changes have been made to the structure or

*This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

7. **Opening Protection:** What is the **weakest** form of wind borne debris protection installed on the structure? **First**, use the table to determine the weakest form of protection for each category of opening. Second, (a) check one answer below (A, B, C, N, or X) based upon the lowest protection level for ALL Glazed openings and (b) check the protection level for all Non-Glazed openings (.1, .2, or .3) as applicable.

Opening Protection Level Chart			Glazed Op	Non-Glazed Openings			
openi form	an "X" in each row to identify all forms of protection in use for each ng type. Check only one answer below (A thru X), based on the weakest of protection (lowest row) for any of the Glazed openings and indicate eakest form of protection (lowest row) for Non-Glazed openings.	Windows or Entry Doors	Garage Doors	Skylights	Glass Block	Entry Doors	Garage Doors
N/A	Not Applicable- there are no openings of this type on the structure				X		\times
Α	Verified cyclic pressure & large missile (9-lb for windows doors/4.5 lb for skylights)			X		X	
В	Verified cyclic pressure & large missile (4-8 lb for windows doors/2 lb for skylights)						
С	Verified plywood/OSB meeting Table 1609.1.2 of the FBC 2007						
D	Verified Non-Glazed Entry or Garage doors indicating compliance with ASTM E 330, ANSI/DASMA 108, or PA/TAS 202 for wind pressure resistance						
N	Opening Protection products that appear to be A or B but are not verified						
IN	Other protective coverings that cannot be identified as A, B, or C						
Х	No Windborne Debris Protection	X	X				

- A. Exterior Openings Cyclic Pressure and 9-lb Large Missile (4.5 lb for skylights only) All Glazed openings are protected at a minimum, with impact resistant coverings or products listed as wind borne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level A in the table above).
 - Miami-Dade County PA 201, 202, and 203
 - Florida Building Code Testing Application Standard (TAS) 201, 202, and 203
 - American Society for Testing and Materials (ASTM) E 1886 and ASTM E 1996
 - Southern Standards Technical Document (SSTD) 12
 - For Skylights Only: ASTM E 1886 and ASTM E 1996
 - For Garage Doors Only: ANSI/DASMA 115

☐ A.1 All Non-Glazed openings classified as A in the table above, or no Non-Glazed openings exist
☐ A.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level B, C, N, o
X in the table above
A 2 One or More Non Clazed Openings is classified as Level R. C. N. or V in the table above

- △ A.3 One or More Non-Glazed Openings is classified as Level B, C, N, or X in the table above
- B. Exterior Opening Protection- Cyclic Pressure and 4 to 8-lb Large Missile (2-4.5 lb for skylights only) All Glazed openings are protected, at a minimum, with impact resistant coverings or products listed as windborne debris protection devices in the product approval system of the State of Florida or Miami-Dade County and meet the requirements of one of the following for "Cyclic Pressure and Large Missile Impact" (Level B in the table above):
 - ASTM E 1886 and ASTM E 1996 (Large Missile 4.5 lb.)
 - SSTD 12 (Large Missile 4 lb. to 8 lb.)
 - For Skylights Only: ASTM E 1886 and ASTM E 1996 (Large Missile 2 to 4.5 lb.)
 - ☐ B.1 All Non-Glazed openings classified as A or B in the table above, or no Non-Glazed openings exist
 - B.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level C, N, or X in the table above
 - B.3 One or More Non-Glazed openings is classified as Level C, N, or X in the table above

C. Exterior Opening	Protection-	Wood	Structural	Panels	meeting	FBC	<u> 2007</u>	All	Glazed	openings	are	covered	with
plywood/OSB meeting	the requireme	ents of T	able 1609.1	.2 of the	FBC 2007	7 (Lev	el C in	the 1	table abo	ove).			

- C.1 All Non-Glazed openings classified as A, B, or C in the table above, or no Non-Glazed openings exist
- C.2 One or More Non-Glazed openings classified as Level D in the table above, and no Non-Glazed openings classified as Level N or X in the table above
- ☐ C.3 One or More Non-Glazed openings is classified as Level N or X in the table above

Inspectors Initials AHP Property Address 934 Capri Isles Blvd Venice Sarasota

^{*}This verification form is valid for up to five (5) years provided no material changes have been made to the structure or inaccuracies found on the form.

☐ N. Exterior Opening Protection (unverified shutter s	ystems with no documenta	ation) All Glazed openings are protected with						
protective coverings not meeting the requirements of Answer "A", "B", or C" or systems that appear to meet Answer "A" or "B' with no documentation of compliance (Level N in the table above).								
☐ N.1 All Non-Glazed openings classified as Level A, B, C, o	r N in the table above, or no N	on-Glazed openings exist						
 N.2 One or More Non-Glazed openings classified as Level I table above 	D in the table above, and no No	on-Glazed openings classified as Level X in the						
☐ N.3 One or More Non-Glazed openings is classified as Leve	el X in the table above							
X. None or Some Glazed Openings One or more Glazed	ed openings classified and L	evel X in the table above.						
MITIGATION INSPECTIONS MUST B Section 627.711(2), Florida Statutes, provi	~							
Qualified Inspector Name: Alexander Hernandez Piedra	License Type: Home Inspection	License or Certificate #: HI15079						
Inspection Company:	Tromo mopostion	Phone:						
Wind Mitigation Network LLC		239-351-5531						
Maindividual or entity who knowingly or through gross ne	es who has completed the statur and completion of a proficience Statutes. 1 489.111, Florida Statutes. atutes. 1 atutes. 1 atutes. 1 ssing the necessary qualifications. 1 section 489.111, Florida Statutes and notest employee who possessed and I personally performed by ecceptable (N/A (print name)) 1 pate:	ons to properly complete a uniform mitigation tatutes, or professional engineer licensed of through employees or other persons. s the requisite skill, knowledge, and I the inspection or (licensed) perform the inspection of inspector) 01/26/2023 r fraudulent mitigation verification form is						
subject to investigation by the Florida Division of Insurance appropriate licensing agency or to criminal prosecution. (Secretifies this form shall be directly liable for the misconduct performed the inspection.	e Fraud and may be subje ection 627.711(4)-(7), Flor	ct to administrative action by the ida Statutes) The Qualified Inspector who						
Homeowner to complete: I certify that the named Qualified residence identified on this form and that proof of identification								
Signature:I	Date:01/26/2023	3						
** Master Association / NA								
An individual or entity who knowingly provides or utters a obtain or receive a discount on an insurance premium to w of the first degree. (Section 627.711(7), Florida Statutes)								
The definitions on this form are for inspection purposes on as offering protection from hurricanes.	ly and cannot be used to co	ertify any product or construction feature						
Inspectors Initials <u>AHP</u> Property Address <u>934 Capri Isle</u>	es Blvd Venice	Sarasota						
*This verification form is valid for up to five (5) years provinaccuracies found on the form.	ided no material changes	have been made to the structure or						
OIR-B1-1802 (Rev. 01/12) Adopted by Rule 69O-170.0155		Page 4 of 4						







Subject Property Elevation Elevation







Elevation Elevation Elevation







Elevation Elevation Elevation





8D Nails Observed

8D Nails Observed

< 6" Nail Spacing








15/32" Roof Decking

SWR Verified

Clip RTW Connection








Impact Rated Door(s)

Unprotected Opening







Impact Verification



Clip RTW Connection